

DESCRIPTION

- Documentation of general sms delivery on kannel apis for internal tool.

ENDPOINTS

- <https://general-sms-kannel-internal.snwolley.com/sms/general/> : general sms delivery information
- <https://general-sms-kannel-internal.snwolley.com/sms/route/> : sms delivery by route
- <https://general-sms-kannel-internal.snwolley.com/sms/submit/> : sms counts by submit
- <https://general-sms-kannel-internal.snwolley.com/sms/mtnmsg/> : sms delivery on mtn route
- <https://general-sms-kannel-internal.snwolley.com/sms/mtnnpontu2/> : sms delivery on mtnnpontu2 route
- <https://general-sms-kannel-internal.snwolley.com/sms/mtnnpontu3/> : sms delivery on mtnnpontu3 route
- <https://general-sms-kannel-internal.snwolley.com/sms/mtnnpontu/> : sms delivery on mtnnpontu route
- <https://general-sms-kannel-internal.snwolley.com/sms/rsms/> : sms delivery on rsms route
- <https://general-sms-kannel-internal.snwolley.com/sms/vodafone/> : sms delivery on vodafone route

REQUEST

- All the endpoints accept `start_date` and `end_date` as parameters.
- Default for `start_date` and `end_date` is the current date. Pass datetime objects for specific date intervals
 - `start_date`
 - `end_date`
- <https://general-sms-kannel-internal.snwolley.com/sms/general/>
 - **POST REQUEST EXAMPLE (PYTHON)**

```
json_payload = {  
    "start_date" : " ",  
    "end_date"   : " "
```

```
}  
req = requests.post("https://general-sms-kannel-  
internal.snwoolley.com/sms/general/", json=json_payload)
```

◦ RESPONSE EXAMPLE

```
{  
  "code": 200,  
  "page_count": 955872.0,  
  "submit_count": 926313,  
  "total_acknowledged": "12.793947618137713%",  
  "total_delivered": "84.25629349906565%",  
  "total_expired": "0.6950134565746136%",  
  "total_undelivered": "2.2546374713514763%"  
}
```

◦ RESPONSE CODES

response code	response
200	ok
500	search failed, Incorrect date format